

SAFETY DATA SHEET

mira x-plan

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

mira x-plan

Product no.

2213991

Unique formula identifier (UFI)

VWEK-SOUD-X008-0DUS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

spartelmasse

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

mira byggeprodukter a/s

Egegårdsvej 2

4621 Gadstrup

+45 46 19 19 46

www.mira.eu.com

Contact person

E-mail

info@mira.eu.com

SDS date

2021-04-21

SDS Version

2.0

Date of previous version

2021-03-11 (1.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.

Eye Dam. 1; H318, Causes serious eye damage.

STOT SE 3; H335, May cause respiratory irritation.

2.2. Label elements

Hazard pictogram(s)







Signal word

Danger

Hazard statement(s)

Causes skin irritation.

May cause respiratory irritation.

Causes serious eye damage.

Safety statement(s)

General

P102, Keep out of reach of children.

Prevention

P261, Avoid breathing dust.

P280, Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301+P310, IF SWALLOWED: Immediately call a POISON CENTER / doctor.

P305+P351+P338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

-

Disposal

P501, Dispose of contents/container to an approved waste disposal plant.

▼ Hazardous substances

Sand

Cement, alumina, chemicals

Calcium sulfate

Cement, portland

White mineral oil (petroleum)

Flue dust, portland cement

p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)

2.3. Other hazards

Additional labelling

Not applicable

▼ Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

The product contains quartz; working processes in which respirable quartz dust can be developed are covered by the EU cancer Regulation.

SECTION 3: Composition/information on ingredients

▼ 3.2 Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Cement, alumina, chemicals	CAS No.: 65997-16-2	10-15%		
Circinicals	EC No.: 266-045-5			
	REACH:			
	Index No.:			



Composed in cartle and		1 20/	Chin Cone 1D 11217	
ement, portland	CAS No.: 65997-15-1	1-3%	Skin Sens. 1B, H317 Skin Irrit. 2, H315	
	EC No.: 266-043-4		Eye Dam. 1, H318	
	REACH:		STOT SE 3, H335	
	T N			
	Index No.:			
Flue dust, portland cement	CAS No.: 68475-76-3	<1%	Skin Irrit. 2, H315 Skin Sens. 1, H317	
	EC No.: 270-659-9		Eye Dam. 1, H318	
	REACH: 01-2119486767-		STOT SE 3, H335	
	17-XXXX			
	Index No.:			
p-toluenesulphonic acid	CAS No.: 104-15-4	<0.0015%	STOT SE 3, H335	
(containing a maximum of	C/13 (101. 104 13 4		Eye Irrit. 2, H319	
5 % H2SO4)	EC No.: 203-180-0		Skin Irrit. 2, H315	
	REACH: 01-2119538811- 39-XXXX			
	Index No.: 016-030-00-2			

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available. Other information

Chromium-reduced Portland cement has been used, which ensures that the content of water-soluble chromium Cr (VI) is below 2 mg / kg for a minimum of 10 months from the packing date, under dry and normal storage conditions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns



Not applicable

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Sulphur oxides.

Some metal oxides.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Collect spills carefully. Moist the material with water in order to prevent the formation and propagation of dust. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

▼ 6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

▼7.1. Precautions for safe handling

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

▼ 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Powder trickling out onto the floor or onto other containers must be prevented.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Store in a closed original container in a dry and well-ventilated place.



Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

_

Cement, portland

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020)

DNEL

No data available

PNEC

No data available

▼ 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

▼ General recommendations

If possible, avoid working processes where respiratory quartz dust may be developed.

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼Appropriate technical measures

In connection with work processes in which respirable quartz dust can be developed e.g. when cutting and drilling in concrete, extracted air must not be recycled according to EU Cancer Regulation.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Work situation	Туре	Class	Colour	Standards	
	For dusty wo use a dust m				
	with particle				
	filter P2.				

Skin protection

Work situation	Recommended	Type/Category	Standards
	Remove soiled clothing and wash skin thoroughly with soap and water when work is complete.		

mira x-plan Page 5 of 12



Hand protection

	Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
		Protective gloves made of eg PVC, neoprene and vinyl				
Ξує	e protection					
	Work situation	Туре		Standards		

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form

Powder

Colour

Gray

Odour

Testing not relevant or not possible due to nature of the product.

Safety glasses

Odour threshold (ppm)

Testing not relevant or not possible due to nature of the product.

рΗ

11-13 (20°C)

Density (g/cm³)

1450000.00

Viscosity

Does not apply to solids.

Phase changes

Melting point (°C)

Testing not relevant or not possible due to nature of the product.

Boiling point (°C)

Does not apply to solids.

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Vapour density

Does not apply to solids.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Evaporation rate (n-butylacetate = 100)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

Does not apply to solids.

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

Explosion limits (% v/v)



Does not apply to solids.

Explosive properties

Testing not relevant or not possible due to nature of the product.

Oxidizing properties

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

▼ 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

No special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

▼ Acute toxicity

v	Nhite mineral oil (petroleum)
Test method	
Species F	Rat
Route of exposure	Oral
Test L	LD50
Result 5	5000.00 mg/kg
Other information	
Product/substance	White mineral oil (petroleum)
Test method	
Species F	Rabbit
Route of exposure	Dermal
Test L	LD50
Result 2	2000.00 mg/kg



Other information	
Product/substance	White mineral oil (petroleum)
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50 (4 hours)
Result	5000.00 mg/m³
Other information	

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ Other information

Sand has been classified by IARC as a group 1 carcinogen.

SECTION 12: Ecological information

▼ 12.1. Toxicity

Product/substance	Calcium sulfate
Test method	
Species	Fish
Compartment	
Duration	No data available.
Test	NOEC



Result 3163 mg/L Cheer information Product/substance Method Compartment Duration 48 hours Result 100.00 mg/L Cher information Product/substance Method Species Fish Compartment Duration 96 hours Test Cs0 Result 100.00 mg/L Cherinformation Test method Test method <th col<="" th=""><th></th><th></th></th>	<th></th> <th></th>		
Product/substance Test method Species Daphnia Compartment Test Result 100.00 mg/L Other information Product/substance Product/substance Species Species Species Test Result 100.00 mg/L Other information Test method Fish Compartment Duration 96 hours Test Result 100.00 mg/L Other information Test Product/substance White mineral oil (petroleum) Test method Test Compartment Test Product/substance Jesion Account Test Result 100.00 mg/L Other information Test Product/substance Account Account Test Product/substance Account Test method Test Test method Test m	Result	3163 mg/L	
Test method Formartment Duration Als hours Test Result Product/substance Fish Compartment Species Fish Compartment Duration Fish Compartment Duration Formation Formation Formation Formation Test Compartment Duration Jest Also Also Also Also Also Also Compartment Duration Test Result Also Also Also Also Compartment Duration Test Also Also Also Compartment Duration Test Also Also Also Compartment Test Product/substance Also Also Also Compartment Duration Test method Test metho	Other information		
Species Compartment Fust Result Outnoring White mineral oil (petroleum) Foreit Ses Fore	Product/substance	White mineral oil (petroleum)	
Compartment Duration 48 hours Test Result 100.00 mg/L Other information Product/substance Fish Compartment Duration 96 hours Test Pouration 96 hours Test Result 100.00 mg/L Other information Test Product/substance 100.00 mg/L Other information Test west Product/substance 100.00 mg/L Compartment Test west Product/substance 200.00 mg/L Compartment Test west Test	Test method		
Duration Result 10.00 mg/L Chere information Product/substance White mineral oil (petroleum) Species Fish Compartment Duration 96 hours Result 100.00 mg/L Chere information Product/substance Mitte mineral oil (petroleum) Test method Species Algae Compartment Duration 2 hours Duration 2 hours Test Bourstone Test Compartment Duration 2 hours Test Duration 2 hours Test Test Test Test Test Test Test	Species	Daphnia	
Test Result 100.00 mg/L Other information Product/substance White mineral oil (petroleum) Species Fish Compartment Duration 96 hours Test (C50 Result 1000.00 mg/L Other information Test (C50 Result 1000.00 mg/L Other information Test method Other information Test (C50 Result 1000.00 mg/L Other information Test (C50 Algae Compartment Duration 101 Test method	Compartment		
Result 10.00 mg/L Other information Froduct/substance White mineral oil (petroleum) Test method Species Fish Compartment Duration 96 hours Test 100.00 mg/L Result 100.00 mg/L Other information Froduct/substance White mineral oil (petroleum) Test ethod Test ethod Test method Te	Duration	48 hours	
Other information Product/substance White mineral oil (petroleum) Test method Species Fish Compartment Duration 96 hours Test LC50 Result 1000.00 mg/L Other information Product/substance White mineral oil (petroleum) Test est method Test method Test method Test method Duration 1000.00 mg/L Test method Test method	Test		
Product/substance Test method Species Fish Compartment Duration 96 hours Test Result 1000.00 mg/L Other information Product/substance Species Algae Compartment Species Algae Compartment Duration Test Compartment Test Species Algae Compartment Duration Test Compartment Duration Test Species Algae Compartment Duration Test Duration Test Duration Test Duration Test	Result	100.00 mg/L	
Test method Species Fish Compartment Duration 96 hours Test 1000.00 mg/L Cother information Product/substance White mineral oil (petroleum) Test method Species Algae Compartment Duration 12 hours Test method Test m	Other information		
Species Compartment Duration 96 hours Co50 Result 1000.00 mg/L Other information Product/substance Species Algae Compartment Duration 72 hours Test Result 100.00 mg/L Other information Test method Ourpartment Test method 100.00 mg/L Ourpartment Test method 100.00 mg/L	Product/substance	White mineral oil (petroleum)	
Compartment Duration 96 hours Test LC50 Result 1000.00 mg/L Other information Product/substance White mineral oil (petroleum) Test method Species Algae Compartment Duration 72 hours Test Result 100.00 mg/L	Test method		
Duration96 hoursTestLC50Result1000.00 mg/LDriver informationTest methodSpeciesAlgaeCompartmentDuration72 hoursTestTestResult100.00 mg/L	Species	Fish	
Test C50 Result 1000.00 mg/L Other information Product/substance White mineral oil (petroleum) Test method Species Algae Compartment Duration 72 hours Test Result 100.00 mg/L	Compartment		
Result 1000.00 mg/L Other information Product/substance White mineral oil (petroleum) Species Algae Compartment Duration 72 hours Test Result 1000.00 mg/L	Duration	96 hours	
Other information Product/substance White mineral oil (petroleum) Species Algae Compartment Duration 72 hours Test Result 100.00 mg/L	Test	LC50	
Product/substance Test method Species Algae Compartment Duration 72 hours Test Result 100.00 mg/L	Result	1000.00 mg/L	
Test method Species Algae Compartment Duration 72 hours Test Result 100.00 mg/L	Other information		
SpeciesAlgaeCompartmentDuration72 hoursTest100.00 mg/L	Product/substance	White mineral oil (petroleum)	
Compartment Duration 72 hours Test Result 100.00 mg/L	Test method		
Duration 72 hours Test Result 100.00 mg/L	Species	Algae	
Test Result 100.00 mg/L	Compartment		
Result 100.00 mg/L	Duration	72 hours	
100.00 Hig/ E	Test		
Other information	Result	100.00 mg/L	
	Other information		

▼12.2. Persistence and degradability

Product/substance	White mineral oil (petroleum)
Biodegradable	Yes
Test	
Result	60%

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment



This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

No special

SECTION 13: Disposal considerations

▼ 13.1. Waste treatment methods

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

17 09 Other construction and demolition wastes (including mixed wastes) containing dangerous

03 substances - Unhardened material

17 09 Mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17

04 09 03 - Fully hardened material

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 - 14.4

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

Not applicable

IMDG

Not applicable

IATA

Not applicable

"MARINE POLLUTANT"

No

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Restrictions for application

No special

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Not applicable

Additional information

Not applicable

▼ Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.



Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP). Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H317, May cause an allergic skin reaction.

H315, Causes skin irritation.

H318, Causes serious eye damage.

H335, May cause respiratory irritation.

H304, May be fatal if swallowed and enters airways.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit.

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the substance/mixture is based on:



The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The safety data sheet is validated by

Reyhaneh R. Kanafi

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en

mira x-plan Page 12 of 12