



Application areas

- ✓ Wall
- ✓ Floor
- ✓ Wet room
- ✓ Indoors
- ✓ Outdoors

Substrate

- ✓ Concrete
- ✓ Tiles
- ✓ Fiber mat
- ✓ Plast
- ✓ Metal
- ✓ Wooden boards



3690 one-seal

One-component mounting glue for 4500 vapour mats, tiles and clinkers as well as metal and plast.

- **Rapid hardening**
- **Adhere to most substrates**
- **Withstands constant water load**

Use 3690 one-seal for gluing 4500 vapourmat, overlapping, pipe sleeves and similar products. Can also be used to glue tiles, metal and plastic when material has been cleaned.

3690 one-seal is supplied in 300 ml plast cartridge.

Product description

Ready-mixed glue in cartridge that adheres to most substrate.

Technical data

Density at 20°C	1.46 kg/l
Drying time at 23°C and 50% RF:	
- surface dry	20-40 min.
- setting time	3-24 hours
Recommended working temperature:	+5-40°C
Consumption (average):	10-12 m edge of mat per cartridge

Application areas

For bonding 4500 vapourmat overlapping and sealing. Can also be used for gluing on concrete, wood, tiles and clinker, metal and plastic when material has been cleaned. Can be applied with success for mounting bathroom equipment such as panels etc. on substrates with sufficient strength.

Pre-treatment of substrate

Stainless steel and plastic drains are cleaned with acetone, plastic must be sanded before gluing. To ensure quick and effective gluing when applying on mat / plast, the substrate must be moistened with a wet sponge before application.

Application

4500 vapourmat

Moisten 4500 vapourmat around the edges then apply 3690 one-seal and fill out with glue trowel. Use enough glue to fully cover the whole area. Press upper mat into the glue.

On other surfaces

Apply 3690 one-seal on cleaned substrate and spread with glue trowel. Press items against each other.

Working Environment

Product is not subject to REACH-registration.

Reference to safety data sheet.

Packaging

300 ml cartridge.

Lagring og transport

Transport and store dry and cold. Product will maintain technical specifications minimum 24 months from production date in unopened packing.

See www.mira.eu.com for information on mira levelling compounds, screeds, waterproofing, tile adhesives, tile fixing and grouting