



7360 tile sealer

Neutral impregnation of joints, absorbent tiles such as terracotta and non-polished natural stones, like marble, granite, slate, limestone etc.

- Penetrates into absorbent substrate
- Provides a dirt repelling surface
- Maintains the appearance of the surface
- Ready-mixed - ready for use

Thin liquid surface protection that penetrates the absorbent substrate and provides dirt repelling surface without altering the appearance of the surface. However, some natural stones may get some depth colour. The surface treatment is repellent to dirt, liquids such as coffee etc. Waste should be removed immediately to prevent drying into the surface.

7360 tile sealer is supplied in 0.5 liter bottle.



Application areas

- ✓ Joints
- ✓ Absorbent tiles
- ✓ Non-polished natural stones such as marble, granite, slate, limestone, etc.

Product description

Easy-flowing surface protector.

Technical data

Setting time	
(dependent on temperature condition):	4-6 hours
Recommended storage/working temperature:	10-20°C
Consumption:	1 liter is sufficient for 6-20 m ²

Working environment

Product is not subject to REACH registration (EU) 1272/2008. Normal safety conditions for handling chemical substances must be followed.

Reference to product safety data sheet.

Packing

0.5 l plastic bottle.

Storage and transportation

Transport and store frost free and chilly. Product will maintain technical specifications minimum 3 years from production date in unopened packing and can be used hereafter.

Application areas

Neutral impregnation for tiles.

Application areas

Used on joints, absorbent tiles and unpolished natural stones, such as marble, granite, slate, limestone, terracotta etc.

Pre-treatment of substrate

The surface must be clean, dry, free of dirt, oil, wax or other surface treatment. Cleaning and grouting must be carried out min. 2 days before surface treatment is started.

Application

7360 tile sealer is applied onto the surface with a viscose cloth or roller. It is important that 7360 tile sealer is distributed evenly onto the entire surface.

Apply in multiple directions to avoid (running) stripes. For highly absorbent surfaces, plenty of 7360 tile sealer must be applied, as subsequent finishing is not possible. After application, any excess 7360 tile sealer should be removed with cloth or the like after 5-10 minutes.

Tools must be cleaned immediately after use with water.

It is recommended to perform a test on a smaller area before treating the entire surface.

During the application, surface gets a wet appearance which dries up within 2-3 days.

Subsequent daily cleaning with 7230 ceramic wash.