

SAFETY DATA SHEET

mira 6997 quick cement

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

mira 6997 quick cement

Product no.

2213991

Unique formula identifier (UFI)

PRCM-UORS-U00J-83NF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cement-based construction products

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

mira byggeprodukter a/s

Egegårdsvej 2

4621 Gadstrup

+45 46 19 19 46

www.mira.eu.com

Contact person

-

E-mail

info@mira.eu.com

SDS date

2021-04-14

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.

Eye Dam. 1; H318, Causes serious eye damage.

STOT SE 3; H335, May cause respiratory irritation.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

- Causes skin irritation.
- Causes serious eye damage.
- May cause respiratory irritation.

Safety statement(s)

General

P102, Keep out of reach of children.

Prevention

- P261, Avoid breathing dust.
- P280, Wear protective gloves/protective clothing/eye protection/face protection.

Response

- P301+P310, IF SWALLOWED: Immediately call a POISON CENTER / doctor.
- P305+P351+P338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

-

Disposal

P501, Dispose of contents/container to an approved waste disposal plant.

Hazardous substances

- Cement, portland
- Flue dust, portland cement
- Calcium diformate
- White mineral oil (petroleum)

2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Cement, portland	CAS No.: 65997-15-1	60-80%	Skin Sens. 1B, H317 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	
	EC No.: 266-043-4			
	REACH:			
	Index No.:			
Flue dust, portland cement	CAS No.: 68475-76-3	15-25%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 STOT SE 3, H335	
	EC No.: 270-659-9			
	REACH: 01-2119486767-17-XXXX			
	Index No.:			

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

Chromium-reduced Portland cement has been used, which ensures that the content of water-soluble chromium Cr (VI) is below 2 mg / kg for a minimum of 10 months from the packing date, under dry and normal storage

conditions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Sulphur oxides.

Carbon oxides (CO / CO₂).

Some metal oxides.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
Avoid direct contact with spilled substances.
- 6.2. Environmental precautions
Avoid discharge to lakes, streams, sewers, etc.
- 6.3. Methods and material for containment and cleaning up
Collect spills carefully. Moist the material with water in order to prevent the formation and propagation of dust.
To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.
- 6.4. Reference to other sections
See section 13 on "Disposal considerations" in regard of handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid direct contact with the product.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.
- 7.2. Conditions for safe storage, including any incompatibilities
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Powder trickling out onto the floor or onto other containers must be prevented.
Recommended storage material
Always store in containers of the same material as the original container.
Storage temperature
Store in a closed original container in a dry and well-ventilated place.
Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.
- 7.3. Specific end use(s)
This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

—
Cement, portland

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020)

DNEL

Product/substance	Calcium diformate
DNEL	337 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects
Product/substance	Calcium diformate
DNEL	4780 mg/kg
Route of exposure	Dermal

Duration	Long term – Systemic effects
-----------------	------------------------------

PNEC

No data available

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above).

Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended.

Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure


No specific requirements

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.


Respiratory Equipment

Work situation	Type	Class	Colour	Standards
	For dusty work use a dust mask with particle filter P2.			

Skin protection

Work situation	Recommended	Type/Category	Standards
	Remove soiled clothing and wash skin thoroughly with soap and water when work is complete.		

Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
	Protective gloves made of eg PVC, neoprene and vinyl			

Eye protection

Work situation	Type	Standards
	Safety glasses	



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form

Powder

Colour

Gray

Odour

Testing not relevant or not possible due to nature of the product.

Odour threshold (ppm)

Testing not relevant or not possible due to nature of the product.

pH

11 - 13 (20°C)

Density (g/cm³)

1450000.00

Viscosity

Does not apply to solids.

Phase changes

Melting point (°C)

Testing not relevant or not possible due to nature of the product.

Boiling point (°C)

Does not apply to solids.

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Vapour density

Does not apply to solids.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Evaporation rate (n-butylacetate = 100)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

Does not apply to solids.

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

Explosion limits (% v/v)

Does not apply to solids.

Explosive properties

Testing not relevant or not possible due to nature of the product.

Oxidizing properties

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

No special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Product/substance	Calcium diformate
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	2650 mg/kg
Other information	
Product/substance	White mineral oil (petroleum)
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	5000.00 mg/kg
Other information	
Product/substance	White mineral oil (petroleum)
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	2000.00 mg/kg

Other information	
Product/substance	White mineral oil (petroleum)
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50 (4 hours)
Result	5000.00 mg/m ³
Other information	

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

No special

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	Calcium diformate
Test method	
Species	Fish
Compartment	
Duration	48 hours
Test	LC50

Result	>1000 mg/L
Other information	
Product/substance	Calcium diformate
Test method	
Species	Daphnia
Compartment	
Duration	48 hours
Test	EC50
Result	>1000 mg/L
Other information	
Product/substance	Calcium diformate
Test method	
Species	Algae
Compartment	
Duration	72 hours
Test	EC50
Result	>1000 mg/L
Other information	
Product/substance	White mineral oil (petroleum)
Test method	
Species	Daphnia
Compartment	
Duration	48 hours
Test	
Result	100.00 mg/L
Other information	
Product/substance	White mineral oil (petroleum)
Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	1000.00 mg/L
Other information	
Product/substance	White mineral oil (petroleum)

Test method	
Species	Algae
Compartment	
Duration	72 hours
Test	
Result	100.00 mg/L
Other information	

12.2. Persistence and degradability

Product/substance	White mineral oil (petroleum)
Biodegradable	Yes
Test	
Result	60%

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

Calcium diformate

LogKoc = 1.49, High mobility potential.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 13 - Sensitising

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

17 09 03 Other construction and demolition wastes (including mixed wastes) containing dangerous substances - Unhardened material

17 09 04 Mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03 - Fully hardened material

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 - 14.4

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

Not applicable

IMDG

Not applicable

IATA

Not applicable

"MARINE POLLUTANT"

No

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

No specific requirements

No special

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Not applicable

Additional information

Not applicable

Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H317, May cause an allergic skin reaction.

H315, Causes skin irritation.

H318, Causes serious eye damage.

H335, May cause respiratory irritation.

H304, May be fatal if swallowed and enters airways.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit.
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the substance/mixture is based on:

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The safety data sheet is validated by

Reyhaneh R. Kanafi

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en